



IK-610LT-RH(B)





SPECIFICATION

MODEL	Unit	IK-610LT-RH(B)
<u>Spindle</u>		
Spindle Bore Diameter		NT50
Diameter of Spindle Nose	mm	Φ128.6
Spindle Motor	Hp	15(Servo motor)
Step of Spindle Speed	stage	2
Spindle Speed (50Hz)	rpm	L: 0 ~ 1000
Spindle Speed (60Hz)	rpm	H:994 ~ 2000
<u>Working Range</u>		
Max Diameter of Cutter	mm	200
Travel	mm	600(up 300 /down 300)
Rapid Travel AC Motor		0.4Kw/0.5Hp AC 3 Phase 4 Poles x 1/40
Rapid Travel Speed	mm/min	177(50Hz) 218(60Hz)
Reversal Slide		2mm/rev → ← 0.01mm
<u>Accessories</u>		
Oil Cooler for Hydraulic / Lubrication Oil		P-BO-750P2TSB-192
Variable-frequency Drive	Kw/Hp	15/20
<u>STANDARD ACCESSORIES</u>		
Spindle Motor		15HP(Servo motor)
Rapid Travel AC Motor		●
Oil Cooler for Hydraulic / Lubrication Oil		●
Variable-frequency Drive		●
Place of Origin		Taiwan
Weight (Approximate)	kg	638
Warranty		1 year (non artificial mistake)

※We reserve the right to modify the design and specifications without notice in advance.