



IK-610-LV





SPECIFICATION

MODEL	Unit	IK-610-LV	
Spindle			
Spindle Bore Diameter		NT50	
Diameter of Spindle Nose	mm	Φ128.6	
Spindle Motor	Hp	10 / 4P	12.5 / 4P
Step of Spindle Speed	stage	6	
Spindle Speed (50Hz)	rpm	102	345
		153	469
		229	705
Spindle Speed (60Hz)	rpm	123	414
		184	563
		275	846
Working Range			
Max Diameter of Cutter	mm	200	
Travel	mm	320(up 220 /down 100)	
Rapid Travel AC Motor		0.4Kw/0.5Hp AC 3 Phase 4 Poles x 1/40	
Rapid Travel Speed	mm/min	177(50Hz)	
		218(60Hz)	
Reversal Slide		2mm/rev → ← 0.01mm	

※We reserve the right to modify the design and specifications without notice in advance.



STANDARD ACCESSORIES		
	10HP / 4P	12.5HP / 4P
Spindle Motor	●	-
	-	●
Rapid Travel AC Motor	●	
OPTIONAL ACCESSORIES (APOLEGAMY)		
Pneumatic Blade Locking Device	○	
Bearing Guide Screw	○	
Pneumatic Leveler	○	
IK-A90 Angular Head	○	
IK-D90 Deep Head	○	
IK-U90 Universal Head	○	
IK-U45 Universal Head	○	
Place of Origin	Taiwan	
Weight (Approximate)	kg	530
Warranty	1 year (non artificial mistake)	

※We reserve the right to modify the design and specifications without notice in advance.

