



IK-915-RV





## SPECIFICATION

MODEL	Unit	IK-915-RV			
<b>Spindle</b>					
Spindle Bore Diameter		NT50			
Diameter of Spindle Nose	mm	Φ128.6			
Spindle Motor	Hp	15(4P)	20(4P)		
Step of Spindle Speed	stage	9			
Spindle Speed (50Hz)	rpm		I	II	III
		A	412	739	554
		B	69	125	94
		C	183	329	246
Spindle Speed (60Hz)	rpm		I	II	III
		A	495	887	665
		B	83	150	113
		C	220	395	296
<b>Working Range</b>					
Max Diameter of Cutter	mm	250			
Travel	mm	600(up 360 /down 240 )			
Rapid Travel AC Motor		0.4Kw/0.5Hp AC 3 Phase 4 Poles x 1/40			
Rapid Travel Speed	mm/min	175(50Hz) 215(60Hz)			
Reversal Slide		2.5mm/rev →    ← 0.02mm			

**※We reserve the right to modify the design and specifications without notice in advance.**



<b>STANDARD ACCESSORIES</b>		
	15HP / 4P	20HP / 4P
Spindle Motor	●	-
	-	●
Rapid Travel AC Motor	●	
<b>OPTIONAL ACCESSORIES (APOLEGAMY)</b>		
Pneumatic Blade Locking Device	○	
Bearing Guide Screw	○	
Pneumatic Leveler	○	
IK-A90 Angular Head	○	
IK-D90 Deep Head	○	
IK-U90 Universal Head	○	
IK-U45 Universal Head	○	
Place of Origin	Taiwan	
Weight (Approximate)	kg	752
Warranty	1 year (non artificial mistake)	

※We reserve the right to modify the design and specifications without notice in advance.

